




# Technical data sheet

27.04.2016  
(Version 2)

Marine diesel engine  
D2862LE446 (V12-1400)

## Performance data <sup>1</sup>

Rated power	1029	kW
Rated power	1400	PS
Speed	2300	rpm
Bore	128	mm
Stroke	157	mm
Displacement	24,24	liter
Rated torque	4272	Nm
Maximum torque	4680	Nm
at speed	1200-2100	rpm
Compression ratio [ε]	17,0	:1
Mean effective pressure	22,15	bar
Mean piston speed	12,04	m/s



## Consumption data <sup>1</sup>

Specific fuel consumption <sup>2</sup>	218	g/kWh
Absolute fuel consumption <sup>2</sup>	267	l/h
Lowest fuel consumption <sup>3</sup>	203	g/kWh

The engine illustrated may not entirely be identical to production standard engine

## Engine description

Operation profile	up to 1000 hours per year at a maximum of 20 % of time at full load   average load < 50 %
Construction	four-stroke marine diesel engine, direct injection, SAE 1 flywheel housing
Cylinders	12 cylinders in V-arrangement, single cylinder heads with wet replaceable cylinder liners
Air system	single-stage turbocharger with charge air intercooler and wastegate
Cooling system	seawater cooled charge air cooler and plate heat exchanger by rubber impeller pump
Oil system	force-feed lubrication by gear pump, lubricating oil cooler in cooling water circuit of the engine
Fuel system	Common Rail injection system with high pressure pump and EDC control, fuel to DIN EN 590
Auxiliary PTO	PTO for hydraulic pump 16 cm <sup>3</sup> (180Nm)
Alternator	three-phase generator with rectifier and transistorized governor, 28 V, 120 A
Starting system	solenoid operated electric starter, 24 V, 7.0 kW
Service	oil change interval 400 operating hours, average TBO 5.000 operating hours
Classification	BV, RINA

**Exhaust status** IMO Tier II, RCD 2013/53/EC, RCD 94/25/EC, EPA Tier 3 recreational, 97/68/EC


<sup>1</sup> values at rated power

<sup>2</sup> Tolerance +5% according to ISO 3046, diesel fuel to DIN EN 590

<sup>3</sup> values on propeller curve

## D2862LE446 (V12-1400)

A - overall width.....	1153 mm
B - overall length.....	2130 mm
C - overall height.....	1230 mm
D - above crank shaft....	765 mm
E - length to flywheel....	1630 mm
Engine weight (dry).....	2270 kg



### Combustion parameters <sup>1</sup>

Intake air temperature (max.)	45 °C
Intake air vacuum (min/max)	30/60 mbar
Intake air volume flow	4255 m <sup>3</sup> /h
Exhaust gas temperature	500 °C
Exhaust gas volume flow	11020 m <sup>3</sup> /h
Exhaust gas mass flow	4850 kg/h
Exhaust back pressure (min/max)	20/80 mbar


### Heat balance <sup>1</sup>

Exhaust gas heat	710 kW
Cooling water heat	685 kW
Intercooler heat	220 kW
Radiation heat	37 kW

### Noise emission <sup>1</sup>

Engine surface noise (Lwa)	103,4 dB(A)
Free exhaust noise (Lwa)	114,1 dB(A)

### Specific fuel consumption<sup>2</sup>



< The rated power is based on reference conditions according to ISO 3046-1 (2002) >

< Intake air temperature, max. 45°C | sea water temperature, max. 32°C >

< Barometric pressure 1000 mbar | air humidity 60% >

< Exponent for propeller curve 2,5 >

**< Engine specifications are subjected to change without prior notice >**

<sup>1</sup> values at rated power

<sup>2</sup> Tolerance +5% according to ISO 3046, diesel fuel to DIN EN 590

<sup>3</sup> values on propeller curve




# Engine curves


27.04.2016  
(Version 2)

D2862LE446 (1029kW@2300rpm) (V12-1400)

Power/torque curves



Absolute fuel consumption<sup>1</sup>



< The rated power is based on reference conditions according to DIN ISO 3046-1 (2002) >

< Exponent for propeller curve 2,5 >

< Engine specifications are subjected to change without notice >

<sup>1</sup> Tolerance +5% according ISO 3046, diesel fuel to DIN EN 590